



## CLEVERTRONICS ECONOMY LITHIUM CIRCLITE



### PRODUCT INFORMATION

Catalogue Number	ECLLED-LI
Description	Economy Lithium Circlite Emergency Luminaire
Construction	Polycarbonate Base, Acrylic Diffuser
Mounting	Surface Mount
Dimensions L x W x H	348mm (Diameter) x 100mm (Height)
Weight	2.3kg
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal Acrylic
Driver	CFL-D13
Lamp(s)	LED Panel Array (30,000hrs), 4000K (default), CRI Ra> 80
Operating Voltage	240V AC; 50Hz (double insulated)
Total lumen output	1390 lm
Power Consumption	0.6 Watts (Standby), 16 Watts (Max)
IP Rating	IP44
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D32 C <sub>90</sub> =D32

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560280	BATT:EcoLith 3.2V 3.0Ah 250mm lead,NoBKT
8003070	PCA: ECLLED-LI #CT10626-L1