

GUARDIAN 2 LED EMERGENCY FLOOD LIGHT

GRLED7FL-L

- Versatile non-maintained LED emergency flood light compliant to AS/NZS2293
- Surface mounted (wall and ceiling) white finish
- IP20 as standard; weatherproof enclosure available with IP65 certification



Performance

System Power	4W
Exit Lumen	616lm
Lm/W	100lm/W
CCT	4000K
CRI	80
Operating Temperature	0 - 40°C
Ingress Protection Rating	IP20
Warranty	3 Years
Lifetime	50,000hrs (L70/B50)


Physical

Dimensions	L350 x W80 x H80mm
Reflector	Plastic (Polycarbonate)
Diffuser	Polycarbonate
Luminaire Colour	White
Weight	1kg
Luminaire Material	Plastic (Polycarbonate)
Driver Location	Integrated
Finish	White
Installation	Ceiling or Wall Mounting

Electrical

Dimming	Non - Dimmable
Voltage	240V
Inrush Current	30A
Inrush Current Duration	20µs
Line Current	0.04A
Electrical Rating	Class 2

Line Drawings



Product Images





Emergency

Battery	LiFePO4
Battery Voltage	6V
Battery Capacity	3200mA
Emergency Mode Wattage	4W
Emergency Mode Lumen	456lm

Accessories

DGLCEM3200/2L12	BATTERY LIFEP04 2C 6.4V 3200MAH STK 200MM LEAD JST-ST-2P CON
GRWPENCL	GUARDIAN LED WEATHERPROOF IP65 ENCLOSURE

Line Drawings



Product Images

