


DISCUS

DISC30W400R

SAP CODE: 2001939




30W, Ultra-slim, Weather Resistant, Tritone LED Oyster

A sleek, aesthetically designed oyster with a slim body profile for both indoor and outdoor applications.



Photometric Diagram



Unit: cd

 - C0/180 116.1deg
 - C90/270 115.5deg

KEY INFORMATION

Lumen Output	2800 / 3040 / 2910lm
Input Power	30W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	*Phase-Cut Dimming
Fitting Colour	WHITE
Warranty	5yr
IP Rating	IP54
IK Rating	IK08
IC Rating	N/A
Rebate Scheme Approvals	Pending Approval

PHOTOMETRIC

Efficacy	93 / 101 / 97lm/W
LED	SMD
CCT	3000 / 4000 / 5700K
CRI	>80
Beam Angle	115°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	60V DC
Power Factor	>0.9
LED Input Current (nominal)	500mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Polycarbonate
Optics	PMMA (acrylic)
Adjustable Angle	N/A
Fixings/Hardware	Mounting Bracket
Connection Type	Terminal Block
Total Weight	0.95kg
Dimensions	Ø400 x 45.5mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 2

*Dimming performance may vary depending on the specifications of the dimmer being used. For best performance use Haneco or KASTA dimmers.