



SKYLUX^{SLIM}

SKYLUX120W-SL

SAP CODE: 2002271



Sleek and effective.

SKYLUX SLIM offers robustness where needed with sleek and streamlined elegance, delivering both form and function. Using the latest LED technology, superior lumen efficacy and sleek diecast aluminium housing, SKYLUX SLIM offers everything you need for highbay lighting applications, whilst reducing your inventory costs.

Its effective fin design ensures optimised life time and performance in retail and industrial applications.

ACCESSORIES

Microwave Motion Sensor HIGHBAY-MS

(SAP 2002281)

- Quick connect
- 12m range with corridor function



Sensor Remote Controller HIGHBAY-REMOTE

(SAP 2002282)

- Required to reprogram sensor



Surface Mount Bracket SKYLUXG4-BRKT

(SAP 2002276)



Prismatic Reflector 120W: SKYLUX120G4-PR

(SAP 2002277)




DALI Converter HBAY-DALI-CONV

(SAP 2002095)

- IP65 rated
- Converts product to be DALI dimmable



PHOTOMETRIC DIAGRAM



Unit: cd

- C0/180 118.7deg
- C90/270 120.5deg

Photometric diagram shown is for SKYLUX120W-SL-50K version only.

POWER/LUMEN SETTINGS

POWER	LUMENS	EFFICACY	CCT
60W	9850 lm	169 lm/W	5000K
70W	11290 lm	166 lm/W	5000K
90W	14369 lm	165 lm/W	5000K
120W	18926 lm	161 lm/W	5000K

SPECIFICATIONS

Total Weight:	1.80kg
Dimensions:	Ø265 x 134mm
Body Material:	Aluminium
Diffuser Material:	Polycarbonate (Clear)
Body colour:	Black
IP Rating:	IP65
IK Rating:	IK08
Beam Angle:	120°
CRI:	>80
SDCM:	<5
Driver:	Integral
Power Lead:	1.5m Rubber Flex & Plug
Input:	100-277V, 50/60Hz
Electrical Classification:	Class 1
Power Factor:	>0.9
Protection:	Overload / Short Circuit
Lifespan:	>50,000hrs @Ta25°C (L70)
Operating Ambient Temperature:	-30 to 50°C
Smart:	KASTA Compatible
Dimming:	0-10V Dimmable