

OBL MINI LED Batten G2

OBL600

- Made with UV resistant polycarbonate body for durability and long product lifetime
- Comes with a frosted opal diffuser for that comfortable and clean ambience.
- Built in 3-way switch for quick and easy adjustment of light levels: OFF, DIM (10W @ 1100Lm) and BRIGHT (15W @ 1680Lm)



LUMEN^{SELECT} | COLOUR^{SELECT}

Performance

System Power	15W, 10W, 10W, 15W
Exit Lumen	1680lm, 1000lm, 1100lm, 1600lm
CCT	4000K, 3000K, 4000K, 3000K
CRI	80
Operating Temperature	0°C to 45°C
Ingress Protection Rating	IP44
Lifetime	54,000hrs (L70/B50)


Physical

Dimensions	L595 x W60 x H70.70mm
Diffuser	Opal
Luminaire Colour	White
Luminaire Material	Plastic (Polycarbonate)
Driver Location	Integrated
Finish	Powder Coated
Installation	Surface Mounting

Electrical

Dimming	Non - Dimmable
Voltage	240V
Line Voltage Frequency	50Hz
Inrush Current	5A
Inrush Current Duration	350µs
Line Current	0.09A
Electrical Rating	Class II

Line Drawings



Product Images



