



DURA

DURA-06
 SAP CODE: 2002138



Photometric Diagram



Unit: cd
 - C0/180 128.1deg
 - C90/270 110.4deg

Durable weatherproof batten

The DURA LED batten features IP65 ingress protection, IK08 impact resistance rating and a unique foldable structure for easy installation.

It is ideal for use in utility-type applications such as car parks, workshops, storerooms and back of house areas.

KEY INFORMATION

Watts	18W
Input Power	10W / 13W / 15W / 18W
Lumen Output	1387lm / 1693lm / 1953lm / 2155lm (4000K) 1431lm / 1768lm / 2050lm / 2356lm (4500K) 1386lm / 1671lm / 1921lm / 2177lm (5000K)
Install	Surface Mount, Suspended
Dimming Options	Non-Dimmable
Fitting Colour	Grey
Warranty	5yr
IP Rating	IP65
IK Rating	IK08
IC Rating	N/A
Rebate Scheme Approval	-

PHOTOMETRIC

Efficacy	139lm / 130lm / 130lm / 120lm (4000K) 143lm / 136lm / 137lm / 131lm (4500K) 139lm / 129lm / 128lm / 121lm (5000K)
LED	SMD
CCT	4000K / 4500K / 5000K
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240Va.c. 50/60Hz
Driver Output Voltage	30-57V
Power Factor	>0.9
LED Input Current (nominal)	200/250/300/350mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	PC
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Clips, Cable gland, Suspension bracket
Connection Type	PA14 Terminals
Total Weight	0.96kg
Dimensions	655 x 102 x 75mm
Operating Ambient Temp.	-10 to 40°C
Electrical Classification	Class 1