





# VISTA

VISTA20/40W12-TRI

SAP CODE: 2001161



Photometric Diagram



Unit: cd  
 - C0/180 110.0deg  
 - C90/270 110.0deg

1200mm, 20/40W  
 Ecoswitch, Tritone,  
 conventional  
 appearance LED batten

An LED replacement for conventional battens with Tritone switchable colour temperature.

### Accessories

SUSPENSION KIT; WIREGUARD

## KEY INFORMATION

Lumen Output <sup>40W</sup>	4540 / 4880 / 4470lm
- Low Power Mode <sup>20W</sup>	2400 / 2510 / 2430lm
Input Power	20 / 40W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Trim Colour	WHITE
Warranty	5yr
IP Rating	IP20
IK Rating	N/A
IC Rating	N/A
Rebate Scheme Approvals	VEET; REES; IPART LCP 43.67

## PHOTOMETRIC

Efficacy <sup>40W</sup>	114 / 122 / 112lm/W
- Low Power Mode <sup>20W</sup>	120 / 125 / 121lm/W
LED	SMD
CCT	4000 / 4700 / 5700K
CRI	>80
Beam Angle	120°

## ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	20-57VDC
Power Factor	>0.9
LED Input Current (nominal)	350-700mA
Useful life @Ta25° (L70)	50,000hr

## CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	Terminal Block PA14
Total Weight	2kg
Dimensions	1221x84x70mm
Operating Ambient Temp.	-30 to 50°C
Electrical Classification	Class 1
Food Grade Approval	HACCP