

# Product datasheet

Specifications



## EVlink PARKING Floor Standing 22KW 1xT2 with Shutter EV CHARGING STATION

EVF2S22P04

! To be discontinued

! To be discontinued on: 30 Dec 2023

! To be end-of-service on: 31 Dec 2025

### Main

Range	EVlink
Product Name	EVlink parking
Product Or Component Type	Charging station
Device Short Name	EVF2
Poles Description	3P + N for power circuit 1P + N for control circuit
Mounting Mode	Floor-standing
Offer Type	Standard
Rated Supply Voltage	230 V AC 50/60 Hz control circuit 380...415 V AC 50/60 Hz power circuit
Earthing System	TT TN IT
Socket-Outlet Number	1
Socket-Outlet Type	Right: T2 with shutter / silver plated contacts
Maximum Supply Current	32 A for T2 with shutter
Max Power	22 kW for T2 with shutter

### Complementary

Control Type	1 red push-button, function: stop 1 green illuminated push-button, function: start/unlock flap
Local Signalling	On charge: 1 LED (green) (flashing) on side Available: 1 LED (green) on front Reserved: 1 LED (orange) on front Not operational: 1 LED (red) on front
Communication Port Protocol	OCPP 1.6
Configuration /Architecture	Clustered architecture Standalone
Operation And Maintenance	Diagnosis capabilities Postponed charge Load management Charge detail records User privilege configuration Circuit breaker status
Web Server	Embedded
Ethernet Service	Configuration via web server

<b>Standards</b>	IEC 61851-1 IEC 61851-22
<b>Product Certifications</b>	ZE Ready EV Ready CE CB
<b>Height</b>	1146 mm
<b>Width</b>	413 mm
<b>Depth</b>	220 mm
<b>Net Weight</b>	50 kg
<b>Colour</b>	Front: white (RAL 9003) Side: grey (RAL 7016)

## Environment

<b>Ip Degree Of Protection</b>	IP54 off load conforming to IEC 61851-1 IP54 on load conforming to IEC 61851-1
<b>Ik Degree Of Protection</b>	IK10 charging station conforming to IEC 61851-22 IK10 socket-outlet conforming to IEC 61851-22
<b>Ambient Air Temperature For Operation</b>	-30...50 °C conforming to IEC 61851-22
<b>Ambient Air Temperature For Storage</b>	-40...80 °C
<b>Operating Altitude</b>	0...2000 m conforming to IEC 61851-22
<b>Relative Humidity</b>	0...95 %

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	38.0 cm
<b>Package 1 Width</b>	45.0 cm
<b>Package 1 Length</b>	128.0 cm
<b>Package 1 Weight</b>	58.0 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)