

Product datasheet

Specifications



T2S socket-outlet subassembly 1-Ph IEC - Wallbox spare part

EVP1HSM41

Main

Range	EVlink
Product Or Component Type	Socket-outlet
Socket-Outlet Type	T2 with shutter
Poles Description	1P + N
[Us] Rated Supply Voltage	220...240 V AC 50/60 Hz
Maximum Supply Current	32 A
Earthing System	Compatible TN Compatible TT Compatible IT with additional isolation transformer on the power supply
Nominal Output Power	7.4 W 32 A
Range Compatibility	EVlink EVlink Wallbox EVH2 charging station

Complementary

Material	Plastic
Product Certifications	CE
Height	110 mm
Width	110 mm
Depth	90 mm

Environment

Ip Degree Of Protection	IP54 conforming to IEC 60529
Ik Degree Of Protection	IK10 conforming to IEC 62262
Ambient Air Temperature For Operation	-30...50 °C
Ambient Air Temperature For Storage	-40...80 °C
Relative Humidity	5...95 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.000 cm
Package 1 Width	15.000 cm
Package 1 Length	40.000 cm
Package 1 Weight	736 g

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.


Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
