

Product data sheet Characteristics

RMXPC3

Connector, Resi MAX, 3P+N, set of 4





Main		
Range	Resi MAX	
Product or component type	Connector	
Accessory / separate part category	Connection accessory	
Quantity per set	Set of 4	
Colour	White (RAL 9003)	

Complementary

Poles description	3P + N	
Mounting mode	Horizontal	
[le] rated operational current	63 A at 40 °C	
Connections - terminals	Screw clamp terminals 135 mm² rigid	
Tightening torque	4 N.m	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	57.0 g	
Package 1 Height	1.5 cm	
Package 1 width	7.5 cm	
Package 1 Length	8.5 cm	
Unit Type of Package 2	S02	
Number of Units in Package 2	25	
Package 2 Weight	1.81 kg	
Package 2 Height	15 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.