

Product data sheet

Characteristics

WMC532

Metal Clad, Switched Socket Outlet Combination, 2 Gang, 32A, 500V, 5 Round Socket



Main

Range of product	Series A Wilco
Product brand	Clipsal
Device application	Power supply

Complementary

Number of poles	5
Number of modules	3
Number of power socket outlets	1 protective cover
[In] rated current	32 A
[Ue] rated operational voltage	500 V AC
Device mounting	Surface
Material	Cast aluminium: housing
Depth	120 mm
Width	115 mm
Height	258 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.0 cm
Package 1 Width	11.5 cm
Package 1 Length	25.8 cm
Package 1 Weight	2.22 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Height	24.5 cm
Package 2 Width	25.3 cm
Package 2 Length	29.8 cm
Package 2 Weight	9.2 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile